

## PRODUCT DESCRIPTION:

SmartCare Stone Sealer is a water based penetrating sealer which forms a water repellent transparent coating on the surface. It is suitable for application on porous and non-porous tiles and natural stones. It seals the pores on the surface and reduces water absorption and staining, thus preserving the natural look of the tile or natural stone.



## Advantages:

- **Water Resistance:** Provides low water absorption giving excellent water resistance to the surface
- **Stain Resistance:** The coating prevents stains to penetrate and deposit in the surface thus giving excellent stain resistance to the surface
- **Maintains Natural Look:** The water resistance, stain resistance and transparent coating provides protection to maintain the natural look of the Tile or Natural Stone
- **Easy to Clean:** It helps to easily clean stains on the surface as compared to a non-coated surface
- **Easy to Use:** It is a single component product which can be easily applied with a brush, sponge or sprayer.

## Recommended Usage:

For interior and exterior applications on Tiles and Natural Stones such as marble, granite, limestone, sandstone, brick. It can also be used on cement grout surfaces.

## Available Packs:

1 ltr and 5 ltr

## Shelf Life:

12 months from date of manufacture when stored in original packaging under normal dry conditions

## Shade:

Whitish liquid

## Coverage:

75-100 sq.ft. per litre for 2 coats; Actual Coverage may vary depending on the porosity of the surface

## Application Process:

### Surface Preparation

- Surfaces should be free of standing water, surface dirt, dust, oils, and other contaminants.
- Surface temperature should be between 5-35° C.
- Allow cements, stucco, and mortars to cure for 72 hours before applying sealer.
- To ensure compatibility and the desired water repellent result, a test application is necessary on each surface to be treated.
- Shake the container well for one minute before opening and using the sealer.

### Application Procedure

- Apply Asian Paints SmartCare Stone Sealer with a white sponge, brush, or sprayer. Allow it to penetrate for 10 minutes.
- Wipe-off excess sealer by buffing it with soft white cotton cloth.
- Allow Asian Paints SmartCare Stone Sealer to air cure for 24 hours. The dried covering can be walked on after 6 hours.
- One application is sufficient for most installations. In case of highly porous substrates, a second and third application may be required. Second and third coat must be applied wet on wet conditions.
- Excess material should be wiped from the surface of marble, granite, glazed tile, or rock when applied on horizontal surfaces. Surface looks like original, no change in color of surface after drying.
- Asian Paints SmartCare Stone Sealer cleans easily with fresh water. Clean the application tools with fresh water immediately after use.

## Precautions:

- SmartCare Stone Sealer is strongly alkaline. Protective gloves and eye protection should be worn when using the product.
- Do not take internally.
- Keep out of reach of children.
- It is a final treatment on tile/stone. Polishing or cleaning tile on top of stone sealer coating is not recommended.
- Do not apply on wet areas like swimming pool and wash areas and on surface with temperature below 7 deg Celsius