

Asian Paints Woodtech Termishield

PRODUCT CODE: 5491



WOODTECH TERMISHIELD BENEFITS



ANTI-TERMITE

Protects against termites & borers



USE WITH ALL TOPCOATS

Use with Enamels & all Woodtech topcoats



PENETRATIVE COAT

Does not impart any colour to wood

PRODUCT FEATURES

DURABILITY



✓ EXCELLENT


HIGH

MEDIUM

LOW

COLOURS AVAILABLE

NA




AVAILABLE PACKS



Woodtech Termishield (5491)- 100ml, 200ml, 500ml, 1 ltr, 5 ltrs

COVERAGE

150 Sq. Ft./Ltr/Coat



FINISH

NA

HOW TO APPLY

PRE PAINTING STEPS



1. Sand the wooden surface along the grains using sand paper No. 180, and then 320 or 400. Wipe surface to clean off loose dust particles.

PAINT APPLICATION PROCESS

APPLICATION	PRODUCT CODE	THINNER	DILUTION % (BY VOL)	VISCOSITY (SEC)	RECOATING PERIOD (HRS)
STEP 1 WOODTECH TERMISHIELD 1ST COAT SPRAY/BRUSH/ RAGGING/INJECT	5491	Nil	Nil	BRUSH: 12 -13 SECS RAGGING: 12 -13 SECS SPRAY: 12 -13 SECS INJECT: 12 -13 SECS	2 HRS
STEP 2 WOODTECH TERMISHIELD 2ND COAT SPRAY/BRUSH/RAGGING/ INJECT	5491	Nil	Nil	BRUSH: 12 -13 SECS RAGGING: 12 -13 SECS SPRAY: 12 -13 SECS INJECT: 12 -13 SECS	2 HRS

Note: 1. Do not sand the Woodtech Termishield Coat
2. Surfaces treated with Woodtech Termishield must always be coated with Asian Paints Enamels or Woodtech Topcoats
3. For over coating with any Woodtech products, allow the "product" to dry for at least 18 hrs.
4. Asian paints Woodtech Termishield must not be polluted with other oil, varnish or the like.
5. The containers should be tightly closed after use.
6. Recoat period is quoted for 30°C and 75% relative humidity, these may vary under different conditions.
7. Viscosity as measured through a Ford cup B4 at 30°C.

Asian Paints Woodtech Termishield



ADDITIONAL INFORMATION

POST PAINTING CARE

- ◆ For removing stains on tiles and metal surfaces, apply NC Thinner on the surface and wipe clean.
- ◆ If stains are difficult to remove, scrapping can be done after applying NC thinner on the stained area.
- ◆ Precautions need to be taken while filling, like masking of adjoining areas with suitable material, as the stains may be difficult to remove if present on wood or coated wooden and wall surfaces.

TECHNICAL DETAILS

- a. Drying time: Surface Dry time: 30 minutes
- b. Flash point: (IS 101/1987, Part 1, Sec 6): above 60°C (140° F)
- c. Stability of thinned paint: Not Applicable
- d. Shelf Life: 36 Months from date of manufacture in original tightly closed container away from direct sunlight and extensive heat.

PRECAUTIONS

- ◆ For optimum performance, Asian Paints Woodtech Termishield must be applied at a temperature between 20°C and 40°C and humidity not above 75%
- ◆ Stir well use.

SAFETY FEATURES

- ◆ Kindly refer to the MSDS for Asian Paints Woodtech Termishield, which gives detailed information on safety measures while handling the paint.
- ◆ Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire
- ◆ Use protective equipment like rubber/polyurathene gloves, safety goggles/glasses, face mask while handling the paint
- ◆ Avoid eye and skin contact. In both cases wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- ◆ Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both cases
- ◆ Dispose in land filling. Do not dispose in any drain or land filling
- ◆ No added Lead, Mercury or Chromium compounds